

STATYS

Redundant design for power availability and site maintainability
from 32 to 1800 A




Ultimate



The solution for

- > Finance, banking and insurance
- > Healthcare sector
- > Telecom & Broadcasting
- > Industry
- > Power generation plants
- > Transport

Advantages



Our dedicated Expert Services for UPS

We offer services to ensure your UPS highest availability:

- > Commissioning
- > On-site intervention
- > Preventive maintenance visits
- > 24-hour call out and rapid on-site repairs
- > Maintenance packages
- > Training



www.socomec.com/services

STATYS provides

- High reliability - internal redundant design to ensure service continuity.
- Flexibility and adaptability to various types of applications.
- Compact design: saves up to 40% of valuable space.
- Easy and secured maintenance.
- Operational security and ease of use. Remote data access in real time and from any location.
- Full support and service.

Static Transfer Switch: user benefits

Supplied by two independent alternate sources, STATYS increases the overall electrical infrastructure availability during abnormal events and programmed maintenance.

- Provides redundant power supply to mission critical loads to increase global uptime of the supplied system.
- Increases the power supply availability by choosing the best power supply quality.
- Provides plant segmentation and prevents fault propagation.
- Allows easy extension and easy infrastructure design, ensuring high availability of the power supply to critical applications.
- Facilitates and secures the maintenance or the modifications of the overall electrical installation (source, distribution, switchboard) while the load is kept supplied.

STATYS also provides protection against:

- Main power source outage.
- Failures in the upstream power distribution system.
- Failures caused by faulty equipment supplied by the same source.
- Operator errors.

Flexibility

STATYS offers a wide range of single-phase and three-phase systems that suits all types of applications and power supply systems.

Dual or single cord servers, linear or non-linear loads, IT or electromechanics are just some of the load types that STATYS can supply. Wherever a smart power source is needed, whether for existing or new electrical plants, STATYS can be easily installed and efficiently supply the load.

It is available in:

- 2 wires and 2 poles switching, to be connected between phase/neutral or phase/phase.
- 3 wires arrangement without neutral, - for reduced cable costs, - for local zoning of the applications by using insulating transformers,
- 4 wires three-phase arrangement with neutral, with or without neutral pole switching,

STATYS offers:

- Flexible digital control capacity that can adapt to any operational or electrical environment conditions,
- Capability to manage synchronised and non-synchronised sources according to load specificity,
- Advanced Transformer Switching Management (ATSM). If the upstream network has no distributed neutral cable, two upstream transformers or one downstream transformer can be added to create a neutral reference point at the output. For the downstream solution, STATYS, thanks to ATSM, correctly manages the switching to limit inrush current and avoid the risk of spurious breakers.

High reliability - Internal redundant design

Main features:

- Redundant control system using double microprocessor control boards.
- Dual redundant power supplies for control boards.
- Individual control board with redundant power supply for each SCR path.
- Integrates an "auto-hold" feature to ensure load continuity in case of internal failure.
- Redundant cooling with fan failure monitoring.
- Real-time SCR fault sensing.
- Separation of main functions to prevent internal fault propagation.
- Robust internal field communication bus.
- Internal monitoring of sensors to ensure maximum system reliability.

Compact design

- Small footprint and compact units.
- Adjacent or back to back mounting.
- Integrable chassis version for optimal implementation into switchboards.
- Front access for easy maintenance.
- Compact Hot Swap 19" rack system.

Standard features

- A smart and flexible transfer system that can be configured according to the type of load.
- Synchronised and non-synchronised sources compatibility (configurable synchronisation tolerance and switching management).
- Fuse-free or fuse-protected design.
- Output fault current sensing.
- Internal CAN Bus.
- Double maintenance bypass.
- Neutral oversizing for non-linear loads compatibility.
- Embedded Inputs, output and maintenance bypass switches (cabinet version).

Standard communication features

- LCD or user-friendly 7" touch-screen multilingual graphic colour display.
- Slots for communication options.
- Dry-contact interface (configurable voltage-free contacts).
- Ethernet interface for STS monitoring via WEB pages.
- MODBUS TCP.
- Full digital configuration and setting.

Options

- Dry-contact interface. (configurable voltage-free contacts).
- MODBUS RTU RS485.
- PROFIBUS / PROFINET gateway.
- REMOTE VIEW PRO supervision software.

Technical data

| STATYS | 19" rack - hot swap - 1ph | | 19" rack - hot swap - 3ph | | Cabinet - integrable chassis (OEM) | | | | | | | | | | |
|--------------------------------------|--|----|---------------------------|-----|------------------------------------|-----|-----|-----|-----|----------|------|------|------|------|--|
| | 32 | 63 | 63 | 100 | 200 | 300 | 400 | 600 | 800 | 1000 | 1250 | 1400 | 1600 | 1800 | |
| Rating [A] | | | | | | | | | | | | | | | |
| ELECTRICAL SPECIFICATIONS | | | | | | | | | | | | | | | |
| Rated voltage | 120-127/220 240/254 V | | 208-220/380-415/440 V | | | | | | | | | | | | |
| Voltage tolerance | ± 10% (configurable) | | | | | | | | | | | | | | |
| Non-synchronized sources management | configurable up to +/- 180 | | | | | | | | | | | | | | |
| Frequency | 50 Hz or 60 Hz (± 5 Hz (configurable)) | | | | | | | | | | | | | | |
| Number of phases | ph+N or ph-ph (+ PE) | | 3ph+N or 3ph (+ PE) | | | | | | | | | | | | |
| Number of poles switching | 2-pole switching | | 3 or 4-pole switching | | | | | | | | | | | | |
| Maintenance bypass (cabinet version) | interlocked and secured | | | | | | | | | | | | | | |
| Overload | 150% for 2 minutes - 110% for 60 minutes | | | | | | | | | | | | | | |
| Efficiency | 99% | | | | | | | | | | | | | | |
| Admissible power factor | no restrictions | | | | | | | | | | | | | | |
| ENVIRONMENT | | | | | | | | | | | | | | | |
| Operating ambient temperature | 0-40 °C | | | | | | | | | | | | | | |
| Relative humidity | 95% | | | | | | | | | | | | | | |
| Maximum altitude | 1000 m a.s.l. without derating | | | | | | | | | | | | | | |
| Acoustic level at 1 m (ISO 3746) | <45 dBA | | | | ≤ 60 dBA | | | | | ≤ 84 dBA | | | | | |
| STANDARDS | | | | | | | | | | | | | | | |
| Safety | IEC 62310, IEC 60529, AS 62310, AS 60529 | | | | | | | | | | | | | | |
| EMC | C2 category (IEC 62310-2, AS 62310.2) | | | | | | | | | | | | | | |
| Product declaration | CE, RCM (E2376) | | | | | | | | | | | | | | |

Dimensions

| Model | | Range (A) | Width (mm) | Depth (mm) | Height (mm) |
|----------|--------------------------|-------------|------------|--------------------|-------------|
| 1 phase | 19" Rack | 32 - 63 | 483 (19") | 747 | 89 (2U) |
| | | 63 - 100 | 483 (19") | 648 | 400 (9U) |
| 3 phases | Integrable Chassis (OEM) | 200 | 400 | 586 | 765 |
| | | 300 - 400 | 600 | 586 | 765 |
| | | 600 | 800 | 586 | 765 |
| | | 800 - 1000 | 1000 | 950 ⁽¹⁾ | 1930 |
| | | 1250 - 1800 | 910 | 815 | 1955 |
| | Cabinet | 200 | 500 | 600 ⁽¹⁾ | 1930 |
| | | 300 - 400 | 700 | 600 ⁽¹⁾ | 1930 |
| | | 600 | 900 | 600 ⁽¹⁾ | 1930 |
| | | 800 - 1000 | 1400 | 950 ⁽¹⁾ | 1930 |
| | | 1250 - 1600 | 2010 | 815 | 1955 |

(1) Depth does not include handles (+40 mm)